



5 VALVE MANIFOLD DIRECT MTG  
 INLETS : 1/2-14 NPT (FEM)  
 VENTS : 1/4-18 NPT (FEM)  
 MATERIAL OF CONSTRUCTION :  
 SEE 'H-SERIES MATERIAL SPEC'

FOR MATERIAL AND PROCESS SPECIFICATIONS REFER TO GENRIC PROCESS CONTROL SHEET ESSF <b>N/A</b>				ALL DIMENSIONS IN MM [INCHES] UNLESS OTHERWISE STATED			REMOVE ALL SHARP EDGES AND BURRS			 <b>Instrumentation</b> Parker Hannifin plc Instrumentation Products Division Riverside Road Barnstaple, Devon EX31 1NP
FOR PART MARKING DETAILS REFER TO PART MARKING SPECIFICATION ESSF <b>N/A</b>				DRAWING TITLE : <b>5 VALVE MANIFOLD DIRECT MTG          PIPE TO FLANGE          1/2-14 NPT (FEM) INLETS          1/4-18 NPT (FEM) VENTS          BASE VENTED          6000 PSI RANGE          CUSTOMER ASSEMBLY DRAWING</b>			INCH	METRIC	ANGULAR	
THIS DRAWING CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN PLC. THIS DRAWING IS FURNISHED ON THE UNDERSTANDING THAT THE DRAWING AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN. WILL NOT BE USED TO THE DETRIMENT OF PARKER HANNIFIN, AND WILL BE RETURNED UPON REQUEST BY PARKER HANNIFIN.							(.00") ± .015"	(.0)mm ± .3mm	±1/2° ±30°	
ISSUE NO.	<b>1</b>	DRAWN BY:	<b>NICK HOLTON</b>	CHECKED BY : Approvals using electronic <b>'PDM WORKFLOW'</b> (QSP05/25)			GENERAL M/C FINISH 63min CLA/ 1.6mm RA GEOMETRICAL TOL'S TO BS.308 PART 3. ALL THREAD TOLERANCES ARE TO BE IN ACCORDANCE WITH PARKER IPD ESST01.			
E.C.N NUMBER	<b>CUST</b>	DATE DRAWN	<b>22/05/2002</b>	APPROVED BY: Approvals using electronic <b>'PDM WORKFLOW'</b> (QSP05/25)			DO NOT SCALE IF IN DOUBT ASK			
DATE	<b>22/05/2002</b>	SCALE	PROPORTIONAL	DRAWING LOCATED IN PDM SYSTEM						